



SPECS

Frame	SportDrive 6061 Heat Treated Aluminium
Fork	ZOOM 188D, LO, 63mm Travel
Headset	FSA HS NO.10 1-1/8"
Hanger	RBSPR50071

COMPONENTS

Handlebars	Alloy 9Deg Backsweep, 31.8mm Barbore, 680mm Width
Stem	Alloy, 65Mm, +9Deg
Grips/ Tape	Single Density Lock On
Saddle	Ridgeback Metro
Seatpost	Alloy 27.2x350mm
Pedals	Ridgeback Metro

DRIVE TRAIN

Shifters	Shimano Altus SL-M2000 9-Speed
Rear Derailleur	Shimano Altus RD-M2000 9-Speed
Chainset	SportDrive 170Mm, 42t
BB	n/a
Chain	KMC X9E
Cassette	Shimano CS-HG200-9 11-36t

BRAKES

Brakes	Shimano BR-MT200 Hydraulic Brakes
Brake Levers	Shimano BL-MT200 Hydraulic Brakes
Rotors	Shimano SM-RT26, 160mm, 6 bolt

WHEELS & TYRES

Rims	WTB SX19 32h
Hubs	Shimano HB-M4050 / FH-M4050 32h
Spokes	Steel 14g
Tyres	WTB Riddler 700x45c Reflex

E-SYSTEM

Drive Unit	SportDrive MD250S, 250w, 90nm
Battery	SportDrive 418wh
Charger	SportDrive 2AH
Lights	AXA Blueline 30 / B&M ILU SR

FEATURES

- UP TO 55KM RANGE*
- 3:45 HOUR CHARGE TIME (50% TO 100%).
- HIGH POWER MOTOR, IDEAL FOR HILLY AREAS.
- SHIMANO HYDRAULIC DISC BRAKES.
- ADDED COMFORT WITH A SUSPENSION FORK.
- INTEGRATED LIGHTING.

* The image above is for illustration purposes only. Ridgeback reserves the right to change spec, colour, features and price without prior warning.

GEOMETRY	SM	MD	LG
Seat Tube	406	457	508
Top Tube	558	580	600
Frame Reach	390	408	417
Frame Stack	589	599	599
Head Tube	130	140	140
Head Angle	69	69	69
Seat Angle	74	74	73
Chainstay	465	465	465
BB Drop	55	55	55
Wheelbase	1105	1117	1136
Fork Offset	45	45	45
Standover	TBC	TBC	TBC
Stem	65	65	65
Handlebar	680	680	680
Crankarm	170	170	170