



SPECS

Frame	STEPS 6061 Heat Treated Aluminium Internal Battery
Fork	Suntour NEX-E25NLO, 63mm Travel
Headset	ACROS AZX-581, 1-1/8"x1.5"
Hanger	n/a

COMPONENTS

Handlebars	Alloy 9Deg Backsweep, 31.8mm Barbore, 680mm Width
Stem	Alloy, 45mm, 0Deg
Grips/ Tape	Single Density Lock On
Saddle	Ridgeback Metro
Seatpost	Alloy Suspension 27.2x300mm
Pedals	Ridgeback Metro

DRIVE TRAIN

Shifters	Shimano Deore SL-M6000 10-Speed
Rear Derailleur	Shimano Deore RD-M6000 10-Speed
Chainset	Shimano STEPS FC-E6100 170M, 38t
BB	n/a
Chain	KMC E10S
Cassette	Shimano CS-HG500-10 11-42t

BRAKES

Brakes	Shimano BR-MT401 Hydraulic Brakes
Brake Levers	Shimano BL-MT401 Hydraulic Brakes
Rotors	Shimano SM-RT54, 180mm, CL

WHEELS & TYRES

Rims	STARS J20S 32h
Hubs	Shimano HB-M4050 / FH-MT400 32h
Spokes	Steel 14g
Tyres	WTB Venture 700x50c

E-SYSTEM

Drive Unit	Shimano STEPS DU-E6100, 250w, 60nm Torque
Battery	Darfon Internal, 504wh
Charger	Darfon 2A Smartcharger
Lights	Herrmans H-Black MR8 E / B&M ILU SR

FEATURES

- UP TO 185KM RANGE IN ECO MODE*
- THREE ASSIST LEVELS.
- HIGH POWER SHIMANO E6100 MOTOR.
- INTEGRATED 500WH DARFON BATTERY.
- ADDED COMFORT WITH A SUSPENSION FORK.
- INTEGRATED LIGHTING.

* The image above is for illustration purposes only. Ridgeback reserves the right to change spec, colour, features and price without prior warning.

GEOMETRY	MD
Seat Tube	431
Top Tube	590
Frame Reach	411
Frame Stack	603
Head Tube	120
Head Angle	68
Seat Angle	73.5
Chainstay	450
BB Drop	58
Wheelbase	1126
Fork Offset	46
Standover	TBC
Stem	45
Handlebar	680
Crankarm	170